







Enhanced visibility by adopting a diffusion lens



S80LS LED Strobe Signal Light for Forklifts

- · Ø80mm LED strobe signal light
- · Extremely bright signal light that reduces attenuation of the signal light
- Excellent visibility in daytime as bulb or xenon lamp
- Vibration and water resistance product
- Flashing rate: 60-80 flashes/min
- · Materials : Lens-PC, Housing-ABS
- Ambient operating temperature : -30°C to +50°C
- Protect rating: IP65
- · Certificates : CE Compliant, UL Listed


| © Specifications | | | | | |
|------------------|-----------|------------|--------------------|--------|--|
| Model number | Voltage | Current | Certificates | Weight | Color |
| S80LS | DC12V-24V | Max 0.160A | (€ (<u>U</u>) | 0.25kg | R-RedA-AmberG-GreenB-Blue |


* DC type allows free voltage with range of 10V-30V.



Technical Diagram

(Units: mm)







S80LS has an extremely bright signal light that reduces signal attenuation under direct sunlight. Therefore, signal light output of this lamp has excellent visibility similar to a bulb or xenon lamp in daytime.

Wiring Instructions

- External power line standard : UL2095 AWG20(0.5sq×2C) 400mm
- · Product can be wired regardless of polarity

