



S66M1-50 Block

Regional Availability - Global


The S66M1-50 is fully compatible with all industry standard accessories while providing a proven, economical solution for terminating high performance cable. The wide range of mounting accessories allows the S66M1-50 to be installed in almost any environment.



The Category 5e S66 block uses the same center spacing between pairs as voice grade blocks and is fully compatible with all industry standard 66 accessories (such as tools, test adapters, mounting brackets, bridging clips, etc.)




Each pair of S66 clips is slightly closer together, creating additional space between conductors of adjacent pairs for reduced Near-End Crosstalk



Patented Category 5e rated S66 quick clip reduces reactive coupling between positions, improving Near-End Crosstalk (NEXT) performance

Product Information



According to ANSI/TIA/EIA-568-C.1 and ISO/IEC 11801:2002, when terminating category 5e riser or horizontal cable, the individual pairs must have their twists maintained within 13mm (0.5 in.) to the point of termination. When using the category 5e S66M1-50 block, The Siemon Company recommends that both conductors of each pair be inserted through the same slot in the fanning strip and then split to the individual quick clips for termination. By doing this, the pairs will be inserted through every other slot in the fanning strip. When cross-connect wire is installed, the cross-connect pairs can be inserted through the same slots in the fanning strip. Category 5e cross-connect wire must be used to maintain category 5e performance.


Ordering Information

S66M1-50 Block

Part Number	Description
S66M1-50	Pair Capacity 50, Quick Clip: 500, Category 5e height: 254mm (10 in.), width: 86.4mm (3.4 in.) depth: 30.5mm (1.2 in.)

Stand-off Brackets for S66 Blocks


Part Number	Description
S89B	Stand-off mounting bracket, can mount one 25-pair connector on each side
S89D	Stand-off mounting bracket, can mount two 25-pair connectors on each side and four on the block



Lasting Hinge Covers

Part Number	Description
MC4LH-(X)	Hinged protective plastic covers
MC4	Clear snap on cover

Use (X) to specify color: 2 = white, 3 = red, 4 = gray, 5 = yellow, 6 = blue, 7 = green, 8 = violet, 9 = orange



Bridging Clips

Part Number	Description
SA1-(XXXX)	2-position bridging clip
SA1-SS-(XXXX)	2-position bridging clip, stainless steel

Use (XXXX) to specify quantity: 100 = 100/bag, 1000 = 1000/bag

S66™ is a trademark of The Siemon Company



Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

North America P: (1) 860 945 4200	Asia Pacific P: (61) 2 8977 7500	Latin America P: (571) 657 1950/51/52	Europe P: (44) 0 1932 571771	China P: (86) 215385 0303	India, Middle East & Africa P: (971) 4 3689743
---	--	---	--	-------------------------------------	--

Siemon Interconnect Solutions
P: (1) 860 945 4213
www.siemon.com/SIS